


# LED Wall Pack Light

Outdoor Area Lighting | Security Lighting






**This WPD2 Series Rotatable Full Cut-off LED Wall Pack Light have upgraded for security lighting, it's widely used at pathway, hallway, perimeter, patio, entrance, stairway, house, garden, garage, yard, warehouse, factory, store, street, porch. With premium driver and Dust-to-Dawn photocell, this product lasts for 100000 hours and save up 80% on energy and operating costs. Inside with quality Lumileds LED as light sources, it's ideal solution to replace conventional fixtures.**

- Dusk-to-Dawn photocell available - Auto turn on at dusk and off at dawn
  - Unique private slim shape design - Uniform lighting distribution via PC lens
  - Easy and fast installation - Direct mounting on wall or with J-Box
  - High efficiency output - light efficiency is up to 120LPW
  - Waterproof IP65 rating - suitable for all kinds of weather
  - Good energy saving - save 80% electricity cost compared to traditional lamp
  - 5 Years Warranty for whole fixture and power supply
-







## General Specifications

Item No.	ML-WPD2-60W
System Power(±5%)	60W
Electrical Data	
Input Voltage	100-277 VAC
LED Driver	MINGLIGHT Driver
Power Frequency	50/60Hz
Power Factor	>0.9
THD	<20%
Optical Data	
System Efficacy	120(±5%) Lm/W tested based on 5000K Ra70
Luminous Flux (±5%)	7200LM
LED Chip	Lumileds SMD3030
Beam Angle	80°
Light Color	3000K / 4000K / 5000K / 5700K
CRI	>70 Ra
UGR	<19
Temperature Data	
IP Rate	IP65 wet/outdoor
Operating Temp	-40° ~ 131° F (-40° ~ 55° C)
Ambient Temp	-4° ~ 104° F (-20° ~ 40° C)
Storage Temp	-40° ~ 158° F (-40° ~ 70° C) R.H.≤85%
Lifespan	≥50000Hrs (Ta=30°C@L70) Operating
Fixture Material	Die casting Aluminium body
Safety Certification	ETL, DLC
Warranty	5 Years
Dimension & Packing Data	
Product size (LxWxH)	281 x 216 x 110mm (11,06" x 8,50" x 4,33")
Net Weight	13.5 KGS (29.76 LBS)
Gross Weight	15.0 KGS (23.07 LBS)
Carton size (LxWxH)	49.5*35*55cm ( 19,49*15,55*21,65 inch)
Qty/Carton	6 PCS
Loading Qty/20' GP	200 CTNS / 1200 PCS
Loading Qty/40' GP	450 CTNS / 2700 PCS
Loading Qty/40' HQ	540 CTNS / 3240 PCS
L.E.D. vs HPS / MH Equivalence	
LED	60W
HPS / MH	250W

# Dimensions



# Installation Diagram

 <p>1.Loosen both sides screws</p>	 <p>2.Use screwdriver to open the mounting cover</p>	 <p>3.Fixed the mounting box on the J-BOX</p>
 <p>4.Complete the wiring to the power source and ground</p>	 <p>5.Tighten the screws for mounting box</p>	 <p>6.Adjust the fixture's angle through both side screws</p>

## Technical Specifications

### #Certificate

#### RoHS approved

This product is tested by independent lab. with all green material.

#### CE / ETL / DLC approved

This product have passed CE & ETL testing and is fully DLC approved.

#### IESNA LM-79 and LM-80 Testing

Minglight fixture have been tested by independent lab. in accordance with IESNA LM-79 and LM-80 Testing

#### Color Stability:

LED color temperature is warranted to shift no more than 200K in CCT over a 50000 hours.

#### Color Uniformity:

Minglight's range of CCT follows the guidelines of the American National standard for specification for the chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017

### #Installation

#### IES Classification:

80° beam angles, the lighting output produces a oval shape distribution to cover the area.

#### Mounting:

This product is direct mounting on wall mounting or with J-box  
The application including Warehouse, patio, entrance, stairway, house, Garage, outdoor facilities.

### #LED Characteristics

#### Lifespan

100000 hours LED lifespan based on IES LM-80 results and TM-21 Calculation.

#### Color Consistency

7-step MacAdam Ellipse binning to achieve consistent one by one color.

### #Smart Engine

#### Dimming Driver

1-10V Dimming optional

#### Smart Sensor

Photocell optional


### #IP Rating

Ingress Protection rating of IP65  
IP65 for dust and water

#### Greenity:

Mercury or UV free. RoHS compliant components. Package boxes are made with recyclable material.

### #Smart solution options


Description	Pictures	Function
Photocell		Auto turn on at dusk/night and off at dawn/daytime

### #Trouble Shooting

Problem	Possible Cause	Solutions
LEDs stop working	The power line is improperly connected.	Reconnect the power cable.
	The power plug is loose.	Firmly plug the power in.
	The LED driver malfunctions.	Replace with new driver.
	The LED chip is damaged.	Replace with new LEDs.
LEDs flash on and off	The output of the driver is abnormal.	Replace with new driver.
	The LED chip breaks down.	Replace with new LED chip.

## Photometrics

DATA OF LAMP		PHOTOMETRIC DATA      Eff: 121.30 lm/W			
MODEL	WPD2-60W	I <sub>max</sub> (cd)	4110	S/MH (C0/180)	0.84
NOMINAL POWER (W)	60	LOR (%)	100.0	S/MH (C90/270)	1.18
RATED VOLTAGE (V)	220	TOTAL FLUX (lm)	7411.3	η UP, DN (C0-180)	0.3, 54.0
NOMINAL FLUX (lm)	7411.27	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.5, 45.2
LAMPS INSIDE	1	η up (%)	0.8	CIBSE SHR NOM	1.00
TEST VOLTAGE (V)	220	η down (%)	99.2	CIBSE SHR MAX	1.10



**Suggested mounting height for best illumination effect: 10 to 23 feet (3 - 7 meters)**



Wall Pack is widely used in pathway, hallway, perimeter, patio, entrance, stairway, house, garden, garage, yard, warehouse, factory, store, street, porch

## Project Cases of MINGLIGHT

